

Flex.Ability.

Flex-O-Vent™: Universal Ventilation Material

- **Won't absorb moisture, which can freeze and block all ventilation**
- **Easy install by just one person**
- **40 year limited warranty**
- **ASTM E 84 tested**



Specially formulated polyester has been manufactured from recycled material and is recyclable.

You already know the importance of proper attic ventilation and uniform airflow to your building—to meet building codes, to reduce utility costs, and reduce long-term building damage. Flex-O-Vent is the latest product available for your ventilation needs—it helps prevent rain and snow infiltration and its unique anti-wicking properties resist clogging; while at the same time, Flex-O-Vent provides plenty of cooling air flow. It comes in colors that are low visibility with your roof and its flexible design provides a Universal Fit for multiple screw down roof panels.

Flex-O-Vent offers excellent quality, easy installation and extreme durability with a 40-year limited warranty to back it up. All this, at an economical price.

Simply put, Flex-O-Vent is a product highly flexible in application, yet can really do the job for you.

HELPS PREVENT RAIN/SNOW INFILTRATION

EXTREMELY DURABLE POLYESTER

EASY INSTALLATION

FLAME-RESISTANT

CLOG-RESISTANT

TEAR-RESISTANT

ECONOMICAL



FLEX-O-VENT

One element of the Marco WEATHER-TITE™ SYSTEM

Patent pending

Flex-O-Vent

Flexibility, versatility, durability.



Ease of installation.

- 1 size fits most panels.
- Easy one man, two step installation.
- Comes in easy-to-handle 10-foot rolls (mirroring most ridge cap lengths).
- Can be easily cut with scissors or utility knife.
- Double bead of M63 adhesive holds product in place until ridge cap is installed.

High quality means durability.

- Made of extremely durable tear-, flame-, and clog-resistant polyester.
- Due to rubber texture won't scratch roof panels.
- Helps prevent insect, animal and snow infiltration.
- Non-clogging.
- Building code compliant.
- 99% recovery after compression.
- 40 year limited warranty.

Economical.

- Cost is less than many other options.
- So durable, you can forget about replacement costs anytime soon.

Specifications

Net Free Area	19 square inches per Linear Foot-ridge
1-1/2" x 3" x 10'	Rib heights 1 1/4" and lower
Air Permeability	760 Cubic Feet per minute
Cold Cracking	-55°C (-130°F)
Snow Infiltration	0
Tear Strength	3.5 ppi
Tensile Strength	16 psi – Elongation 175%
Compressive Strength	1.8 psi @ 75%
Abrasion	No Damage
100 mpg Wind-driven Rain ..	No Leakage Non-Profile Sensitive

Flex-O-Vent represents yet another Marco Industries technological development in bringing you innovative, higher quality, and more economical products for the metal building industry.

To place your order: [1.800.800.8590](tel:1.800.800.8590) | marcoindustries.com | info@marcoindustries.com



Marco Industries Corporate: 9410 E. 54th Street | Tulsa, OK 74145 | 1.800.800.8590
Marco Industries Canada: 1632 Broder Street | Regina, Sask S4N 7K1 | 1.866.244.7573

MPC0410